


直流电源型


产品特征

工作状态指示：
透明窗红色：失效
电涌防护模块：支持热插拔，维护便捷
遥信功能，订货时指定


CZLB-24



CZLB-110




CZLB-220



技术参数			
额定工作电压Un	24VDC	110VDC	220VDC
最大工作电压Uc	36VDC	220VDC	320VDC
标称放电电流In (8/20μs)	20kA	20kA	20kA
最大放电电流Imax (8/20μs)	40kA	40kA	40kA
电压保护水平Up	<600V	<700V	<800V
过流保护装置	16~25A	25~40A	25~40A
推荐接地铜导线线径	2.5~35mm²	4~35mm²	4~35mm²
响应时间	25ns	25ns	25ns
漏电流	<10μA	<10μA	<10μA
外壳防护等级 (符合IEC60529)	IP 20	IP 20	IP 20
外壳材料 / 阻燃等级 (UL94)	PA66 / V0	PA66 / V0	PA66 / V0
测试标准	GB 18802.1 / IEC 61643-1	GB 18802.1 / IEC 61643-1	GB 18802.1 / IEC 61643-1
产品认证			
防雷性能测试	上海防雷产品测试中心	上海防雷产品测试中心	上海防雷产品测试中心

外形尺寸



71.0mm × 90.0mm × 18.0mm



71.0mm × 90.0mm × 18.0mm



71.0mm × 90.0mm × 18.0mm

典型应用

